

| MODEL | | Universal 43/6 | M 45/6 | Universal 52/8 | M 55/L | HSS 18 | Universal 70/20 |
|---|------------------------------------|---|---|---|-------------|-------------------------------|--|
| Max. Thick- ness | clenched | 6 mm | 6 mm | 8 mm | 4 mm | 12,5 mm | 20 mm |
| Crown Width | | 12 mm | 12 mm | 14 mm | 14 mm | 14 mm | 14 mm |
| Distance be- tween staple centers | minimal | 43-55 mm | 45-54 mm | 52-65 mm | 55-60 mm | 56-76 mm | 70-100 mm |
| Stitching Wire | | alternatively Nr. 24-26 Nr. 26-28 | alternatively Nr. 24-26 Nr. 26-28 Nr. 23 | alternatively Nr. 24-28 Nr. 26-30 Nr. 21-23 Nr. I-III | Nr. 24-26 | Nr. 24-28 and Nr. 21-23 | Nr. 21-24 Nr. III-VI and Nr. 24-30 Nr. I-III |
| Optional Equipment | Standard Stitching Crown Widths | | 14 mm | 5/8/16 mm | | | 16 mm |
| | (Max. Stitching Thick- ness) | | (6 mm) | (3/5/8 mm) | | | (12 mm) |
| | Inner Loop Diameters | 6 mm | | 6/7/8 mm | 7,5 mm | | 6 mm |
| | (Max. Stitching Thick- ness) | 3 mm | | (4/3/3 mm) | (3 mm) | | (4 mm) |
| | Ribbon Wire Crown Widths | | | 10/14 mm | | | |
| | (Max. Stitching Thick- ness) | | | (4/5 mm) | | | |
| Max.speed (per minute per head) | | 170 | 330 | 330 | 200 | 330 | 330 |
| Net weight | | app. 2,0 kg | app. 1,8 kg | app. 4,5 kg | app. 2,1 kg | app. 4,5 kg | app. 8,0 kg |